

HSE-40/SK - Headworn Microphone



Ultralet miniheadset

- Kondensatorkapsel
- Omnidirectional karakteristik
- 3-polet mini XLR hunstik
- Diskret design med ørebøjle
- Udført i silikone; passer til ører i alle former og størrelser
- Kompatibel med lommeseendere TXS-...HSE med 3-polet mini XLR tilslutning
- Ekstern strømforsyning, fx via phantom strømforsyningsadapter EMA-1 eller EMA-300P
- Vindhætte til mikrofon

Technical data:

| | |
|--------------------------------|-------------------------|
| Description | : headband microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : omnidir. |
| System | : back electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 2 kOhm |
| Sensitivity | : 7.9 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 130 dB |
| Power supply | : DC 1.5-9 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 14 g |
| Cable | : - |
| Connection | : 3-pole mini XLR |
| Packing dimensions (W x H x L) | : 0.075 x 0.04 x 0.16 m |
| Gross weight | : 0.06 kg |
| Net weight | : 0.014 kg |