

## TXS-920 - Receiver



**2-kanals trådløs modtager, med UHF PLL teknologi.**

- 2 licensfrie frekvensområder (E bånd: 823-832 MHz og 863-865 MHz)
- 442 kanaler
- Intermodulationsfrie presets, 4 grupper af hver 8 kanaler
- Max. 12 intermodulationsfrie kanaler kan benyttes samtidig (autoscan)
- SYNC funktion til transmission af den valgte frekvens til lommesender TXS-900HSE eller trådløs mikrofon TXS-900HT via infrarødt signal
- Autoscan med intermodulationsgenkendelse
- Ægte diversity system med aftagelige antenner (BNC tilslutning)
- Pilotone squelch
- Volumen- og squelchkontrol
- LCD-indikator for gruppe/kanal, frekvens, RF signalstyrke, AF lydstyrke
- XLR udgang (bal.) og 6,3 mm udgang (ubal.) pr. kanal, mic/line
- 6,3 mm udgang for mixet signal (line)
- 8 V spænding til aktive antenner eller antenne forstærker (fx TXA-875B) er tilgængelige
- Robust metalkabinet
- Strømforsyning medfølger
- 482 mm (19") rack installation ved brug af medfølgende monteringsbeslag

**Der er begrænsninger eller krav i EU! Se venligst bemærkningerne vedrørende trådløse systemer i afsnittet "VIGTIG INFORMATION"! SOUNDCHECK 11/2014**

"The transmission systems of the TXS series are perfectly equipped for the future and with the latest technology ensure an interference-free transmission on a big stage."

+ Easy configuration

+ Interference-free transmission

+ Impressive over greater distances

## Technical data:

Multifrequency	: 1
General information	:
Description	: receiver unit
Carrier frequency range	: 823-832 MHz + 863-865 MHz
Audio frequency range	: 80-18,000 Hz
Channels	: 2
THD	: < 1%
Dynamic range	: ? 100 dB
Latency	:
RF S/N ratio	: ? 100 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	: -
Transmitting power	: -
Operating range	: -
Power supply transmitter	: -
Width transmitter	: -
Height transmitter	: -
Depth transmitter	: -
Weight transmitter	: -
Connections transmitter	: -
Specifications receiver	:
Audio signal receiver	: line: 75 mV, mic: 7 mV (jack, unbal.) line: 150 mV, mic: 15 mV (XLR, bal.) 75 mV (mix)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 420 mm
Height receiver	: 42 mm
Depth receiver	: 183 mm
Weight receiver	: 2 kg
Connections receiver	: 2 x XLR, bal., 2 x 6.3 mm jack, unbal. 1 x 6.3 mm jack, unbal. (mix)