

PAM-10 - Amplifier



PA amplifier,
with zone paging microphone.

- Integrated amplifier 10 W
- Talk button and volume control, speaker connection 4-16 Ohm
- Power supply: \approx 230 V/50 Hz/12 VA
- Dimensions: 167 x 65 x 130 mm
- Mains operation

Technical data:

Low-impedance	: 1
Peak output power	: -
Power rating	: 10 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: 4-16 Ohm
Channels	: 1
Zones	: -
Inputs	: -
Attenuation factor	: -
Frequency range	: 80-12,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: -
THD	: -
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 12 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 167 mm

Height	: 65 mm
Depth	: 130 mm
Rack units, RU	: -
Weight	: 1.14 kg
Connections	: electret gooseneck microphone, omnidirectional polar pattern speaker terminals
Packing dimensions (W x H x L)	: 0.145 x 0.2 x 0.175 m
Gross weight	: 1.35 kg
Net weight	: 1.14 kg