

PA-M4RC - PA Desk Microphone



PA zone paging microphone,
for PA matrix mixing amplifier PA-M224 or PA-M412.

- 4 zone selector switch
- ALL-CALL button
- Plug-in electret gooseneck microphone (3-pole XLR jack)
- Phantom power for gooseneck microphone
- LED indication for signal status
- Power supply via PA-M224 or PA-M412
- Connection to PA-M224 or PA-M412 via RJ45 jack and Cat. 5e network cable (copper, supplied w/o cable), cable length up to 200 m

Technical data:

| | |
|--------------------------------|-----------------------------|
| Description | : PA zone paging microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : - |
| System | : electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : via PA-M224, PA-M412 |
| Operating time | : - |
| Audio frequency range | : 45-15,000 Hz |
| Nominal impedance | : - |
| Sensitivity | : 1 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : 420 mm |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 140 x 65 x 205 mm |
| Weight | : 860 g |
| Cable | : - |
| Connection | : RJ45 |
| Packing dimensions (W x H x L) | : 0.1 x 0.21 x 0.35 m |
| Gross weight | : 1.09 kg |
| Net weight | : 0.86 kg |