

PA-2400RC - PA Desk Microphone



PA zone paging desktop microphone,
for connection to PA-6010Z or PA-6020Z.

- Selection buttons for speaker zones 1-20
- Start/stop function for 6 selectable announcements which are stored in the digital module PA-1120DMT, available at option
- LED indication for various functions
- Automatic chime via microphone announcement button
- Adjustable microphone sensitivity
- 24 V power supply via suitable amplifiers
- RJ45 jacks for connection to additional PA-2400RC with slave/priority switch
- Up to 32 x PA-2400RC can be connected to suitable amplifiers
- Supplied with 3 m connection cable (Cat. 5e)

Technical data:

Description	: PA desktop microphone
Version	: -
Transmission method	: cable
Polar pattern	: -
System	: -
Carrier frequency range	: -
Transmitting power	: -
Power supply	: via PA-6010Z, PA-6020Z
Operating time	: -
Audio frequency range	: -
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 275 x 51 x 156 mm (console housing)
Weight	: 1.4 kg
Cable	: -
Connection	: RJ45 (input/link)
Packing dimensions (W x H x L)	: 0.2 x 0.27 x 0.32 m
Gross weight	: 1.9 kg
Net weight	: 1.56 kg