

ECM-450 - Electret Chime Microphone



Bordmikrofon, med svanehals.

- Elektret, cardioid karakteristik
- Volumenkontrol for tale og signaltone
- Flere forskellige signaltoner
- Automatisk signaltoneaktivering (kan deaktiveres)
- Strømkilder: medfølgende strømforsyning eller batterier (medfølger ikke)
- 1,5 m tilslutningskabel med 6,3 mm jack (i begge ender)

Technical data:

Description	: desktop microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 100-12,000 Hz
Nominal impedance	: 600 Ohm
Sensitivity	: 3.2 mV/Pa
S/N ratio	: ? 40 dB
Max. sound pressure	: -
Power supply	: via encl. power supply or 2 x 1.5 V batt. C size
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 180 x 50 x 130 mm (console housing) 210 mm (length of gooseneck)
Weight	: 925 g
Cable	: 1.5 m
Connection	: 6.3 mm jack low-voltage jack
Packing dimensions (W x H x L)	: 0.19 x 0.105 x 0.27 m
Gross weight	: 1.43 kg
Net weight	: 1.129 kg