


# PA-4120 - PA Amplifier



## PA power amplifier

- 4 x 120 W
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

## Technical data:

100 V	: 1
Low-impedance	: 1
Peak output power	: -
Power rating	: 480 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 4 x 120 W
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: 4 x 120 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: 22Â V/4Â Ohm, 50Â V/21Â Ohm, 70Â V/41Â Ohm, 100Â V/83Â Ohm
Channels	: 4
Zones	: -
Inputs	: 1.2Â V, bal.
Attenuation factor	: -
Frequency range	: 55-17,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 90 dB(A)
Crosstalk attenuation	: -
THD	: < 1%
Phantom power	:
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,400 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 60 A

Admiss. ambient temp.

: 0-40 °C





Width	: 483 mm
Height	: 133 mm
Depth	: 370 mm
Rack units, RU	: 3
Weight	: 25 kg
Connections	: 4 x XLR (inputs), screw terminals (speakers)
Packing dimensions (W x H x L)	: 0.48 x 0.22 x 0.54 m
Gross weight	: 27.6 kg
Net weight	: 25.68 kg