

## PA-1480 - PA Amplifier



### Mono PA power amplifier

- 1 x 480 W
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Temperature-controlled fan, continuously adjustable
- LED indication for clip, protect, overtemperature and output level
- Feed-through output (link)
- Mains operation or 24 V emergency power operation

## Technical data:

100 V	: 1
Low-impedance	: 1
Peak output power	: -
Power rating	: 480 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: 1 x 480 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: 1 x 480 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: 62 V/8 Ohm, 70 V/10 Ohm, 100 V/21 Ohm
Channels	: 1
Zones	: -
Inputs	: 1.2 V, bal.
Attenuation factor	: -
Frequency range	: 35-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 100 dB(A)
Crosstalk attenuation	: -
THD	: < 1%
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,400 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 40 A
Admiss. ambient temp.	: 0-40 °C



Width	: 483 mm
Height	: 88 mm
Depth	: 374 mm
Rack units, RU	: 2
Weight	: 15.2 kg
Connections	: XLR/screw contacts (inputs) screw contacts (speakers)
Packing dimensions (W x H x L)	: 0.54 x 0.18 x 0.48 m
Gross weight	: 17.24 kg
Net weight	: 15.22 kg