

AKB-160 - Amplifier Module

100V



Forstærkermodul, med 100 V output.

- 1 x 40 W
- Lydløs i brug: blæserfrit kølesystem
- Balanceret (XLR) og ubalanceret line-indgang (RCA)
- Højttalerudgang via klemterminaler
- Volumenkontrol
- Metalkabinet med monteringsbeslag

Technical data:

100 V	: 1
Fanless	: 1
Peak output power	: 60 W
Power rating	: 40 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: 40 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 390 mV/26 kOhm, bal.420Â mV/11Â kOhm, unbal.
Attenuation factor	: -
Frequency range	: 17-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: -
THD	: < 1%
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 75 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -

Admiss. ambient temp.

: 0-40 °C





Width	: 213 mm
Height	: 55 mm
Depth	: 238 mm
Rack units, RU	: -
Weight	: 3.2 kg
Connections	: 1 x XLR (line)1 x RCA L/R (line)
Packing dimensions (W x H x L)	: 0.29 x 0.11 x 0.305 m
Gross weight	: 3.6 kg
Net weight	: 3.23 kg