

## TXS-631SET - Wireless Microphone



**Trådløst mikrofonsystem**, med UHF PLL teknologi.

- 1 lommeender, 1 knaphulsmikrofon, 1 modtager, 1 strømforsyning
- Ægte diversity system
- 80 UHF kanaler (863-865 MHz)
- ACT funktion for transmission af valgt frekvens til lommeender via infrarødt signal
- Automatisk søgning
- Volumen og squelchkontrol
- Gain kan justeres på lommeenderen
- Indikator for kanal, antenne A/B, ACT status og AF lydstyrke (modtager), kanal og batteristatus (lommeender)
- Robust metalkabinet (modtager)

**Licensfrit i EU.**

## Technical data:

Multifrequency	: 1
Tie clip microphone	: 1
General information	:
Description	: wireless microphone system
Carrier frequency range	: 863-865 MHz
Audio frequency range	: 50-18,000 Hz
Channels	: 1
THD	: < 0.5%
Dynamic range	: 120 dB
Latency	:
RF S/N ratio	: 105 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	:
Transmitting power	: < 10 mW
Operating range	: $\hat{30}$ m
Power supply transmitter	: 2 x 1.5 V batt. AA size
Width transmitter	: 62 mm
Height transmitter	: 105 mm
Depth transmitter	: 25 mm
Weight transmitter	: 88 g
Connections transmitter	: -
Specifications receiver	:
Audio signal receiver	: 350 mV/10 kOhm (jack) 25 mV/10 kOhm (XLR, bal.)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 152 mm
Height receiver	: 38 mm
Depth receiver	: 120 mm
Weight receiver	: 482 g
Connections receiver	: 1 x 6.3 mm jack, unbal. 1 x XLR, bal.