

BQ-CC55 - eneloop charger



Plug-in quick charger,
from PANASONIC.

- For 1-4 NiMH eneloop rech. batteries, AA size or AAA size
- Charging control for each slot
- Microprocessor-controlled charging control (-ΔU method)
- Safety timer
- Reverse polarity protection, temperature monitoring
- Detection of faulty battery
- LED status indication for each charging slot

Technical data:

Category	: plug-in quick charger
Input voltage	: ∿ 100-240 V/50-60 Hz/300 mA
Output voltage	: 4 x DC 1.5Â V
Output current	: 3.2 A (rech. batt. AAÂ size) 1.2 A (rech. batt. AAAÂ size)
Charging time	: dep. on capacity, size and number: from 0.75Â h on
Trickle charge	: yes
Polarity selection	: -
Switchable output voltage	: -
Reactivation	: -
Connections	: 4 x battery compartment
Cable length	: -
Short-circuit protection	: -
Overload protection	: -
Overheat protection	: yes
Reverse polarity protection	: yes
Detection of faulty battery	: yes
Protective class	: -
Admiss. ambient temp.	: 0-35 °C
Dimensions	: 86 x 76 x 120Â mm
Weight	: 124 g
Position	: -
Other features	: -Î"VÂ method, safety timer, charging control for each slot