

DIB-102 - Direct Box



DI-boxe

Til optimal transmission af signaler fra musikinstrumenter til en mixer eller forstærker. Forstyrrelser, der skyldes tilpasningsproblemer, fx brum, undgås bedst ved brug af en transformerkobling. Indgang og udgang er her galvanisk adskilt.

Til line-enheder benyttes LTR serien! 2-kanals DI-box

- Niveauekontrol (0/-20/-40 dB) for hver kanal
- Ground lift for hver kanal
- Feed-through udgang for hver kanal
- Balanceret transformer
- Robust metalkabinet

tools4music 06/2009 on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

"Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the ever accompanying tool case." **tools4music 02/2010** "The DIB-102 from IMG Stage Line impresses by both the attractive price and the very stable housing. The frequency curve is exemplary."

Technical data:

Description	: DI box
Frequency range	: 15-30,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 50 kOhm
Output signal	: -
Output impedance	: 600 Ohm, XLR50 kOhm, jack
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: 10:1
S/N ratio	: -
Channel separation	: -
THD	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 148 x 50 x 130 mm
Weight	: 755 g
Inputs	: 2 x 6.3 mm jack, unbal.
Outputs	: 2 x 6.3 mm jack, unbal., par. out2 x XLR, bal.
Other features	: -
Width	: 148 mm
Height	: 50 mm
Depth	: 130 mm
Length	: -
Rack units, RU	: -
Weight	: 0.755 kg