

## MSC-115AC/SW - Audio/AC-Cable



Combined mains and XLR cable,  
for facilitating connection, e.g. of active speaker systems to mixers due to 'one-cable' solution.

- Length: 15 m, 75 cm spliced
- XLR cable fitted with XLR plug and XLR inline jack, balanced
- Specification mains cable: H05VV-F3G x 1.5 mm<sup>2</sup>, 2,300 VA max.
- Mains cable fitted with earthed plug and 3-pole IEC inline jack

## Technical data:

|                        |   |
|------------------------|---|
| Intended use           | : mains and XLR cable                                     |
| Connectors             | : 1 x earthed plug to 1 x 3-pole IEC inline jack, 1 x XLR |
| Cable specification    | : H05VV-F3GÂ xÂ 1.5Â mm <sup>2</sup>                      |
| Length                 | : 15 m  |
| Spliced                | : 75 cm   |
| Colour                 | : black   |
| Internal conductor     | : -   |
| Material               | : -   |
| No. of cores           | : -   |
| Cable diameter         | : -   |
| Metre marking          | : -   |
| Minimum bending radius | : -   |
| Shielding              | : -   |
| Shielding value        | : -   |
| Impedance              | : -   |
| Attenuation            | : -   |
| Capacitance            | : -   |
| Power rating           | : 23,000 VA   |
| Rated current          | : -   |
| Packaging              | : -   |
| Weight                 | : 4.22 kg   |
| Position               | : -   |
| Special feature        | : -   |
| Other features         | : -   |