

## TXA-802SR - Receiver



Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz, with Extensive Accessories

- Compatible with portable amplifier systems TXA-624CD/SW, TXA-604/SW and the TXA-820 and TXA-1020 series
- In addition to the combination with TXA-624CD/SW, TXA-604/SW and the TXA-820 and TXA-1020 series, it can also be used as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Can be combined with transmitters and receivers of the ATS-16 series
- Simultaneous operation of up to 4 transmitters with different frequencies (dep. on distance of transmitters, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

2-channel multifrequency receiver,  
with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-800ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system
- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal
- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg



Licence-free in the EU.

## Technical data:

Multifrequency	: 1
General information	:
Description	: receiver unit
Carrier frequency range	: 863.1-864.9 MHz
Audio frequency range	: -
Channels	: 2
THD	: -
Dynamic range	: -
Latency	:
RF S/N ratio	: -
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	: -
Transmitting power	: -
Operating range	: -
Power supply transmitter	: -
Width transmitter	: -
Height transmitter	: -
Depth transmitter	: -
Weight transmitter	: -
Connections transmitter	: -
Specifications receiver	:
Audio signal receiver	: 30 mV (XLR), 730 mV (6.3 mm jack, high), 80 mV (6.3 mm jack, low)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 215 mm
Height receiver	: 50 mm
Depth receiver	: 210 mm
Weight receiver	: 1.2 kg
Connections receiver	: 1 x XLR, bal., 1 x 6.3 mm jack, unbal.