

KU-616T - Horn Driver



Weatherproof horn driver

- 100 V line technique
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1 1/2") mounting flange
- 55 cm connection cable

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 40 W
Power rating (RMS)	: 40/30/20/10/5 W
Impedance	: -
Frequency range	: 160-6,500 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: -
SPL	: 112 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: power selector switch
Housing material	: metal
Colour	: black
Mounting device	: 3.5 cm mounting flange
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 150 mm x 136 mm

Width	: Å~ 150 mm
Height	: -
Depth	: 136 mm
Weight	: 2.2 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: KU-616T/VC
Other features	: weatherproof
Accessories	:
Packing dimensions (W x H x L)	: 0.14 x 0.145 x 0.14 m
Gross weight	: 2.4 kg
Net weight	: 2.195 kg