

# IMC-300T/VA - Omnidirectional Speaker



**IMC-300T/VA - 360° lydoplevelse** Med denne omnidirektionale højttaler er det muligt at fylde relativt store områder. Når højttaleren er monteret i en højde på 4 m får du en homogen lydudstråling, der dækker et område på ca. 200 m<sup>2</sup>. Højttaleren har en fremragende lydkvalitet takket være en 6,5" koaksial højttalerenhed, der i det store kabinet giver optimal lyd med en fyldig bas. Denne højttaler er ideel til både tale og musik og er velegnet til brug i f.eks. butikker, restauranter, kontorer og lagre, hvor der er behov for en diskret højttalerløsning der kan dække store arealer. Højttaleren er EN 54-24 certificeret.

- 100 V: 30/20/10 W
- 2-vejs koaksial højttaler (6,5 ")
- Omnidirektional - Skirer en homogen udstråling af lyden
- Fremragende lyd gengivelse med fyldig bas
- Anbefalet installationshøjde: ca. 4 m
- Hvidlakeret stålkabinet
- Ophængning via stålwire og karabinhager
- Kabelgennemføring (PG11)
- Keramisk terminal

## Technical data:

100 V	: 1
EN 54 certification	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 30/20/10 W
Impedance	: -
Frequency range	: 60-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: 1
Midrange speaker	: -
Tweeter	: 1
Number of speakers	: 2
Speaker size	: 6.5"
SPL	: 83 dB/W/m
Max. rated SPL	: 98 dB
Radiation angle/beam angle	: H: 360°/V: 160°
Radiation angle, horizontal	: 360°
Radiation angle, vertical	: 160°
Features	: -
Housing material	: metal
Colour	: white
Mounting device	: steel rope with snap hook
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: ~ 480 mm x 300 mm
Width	: ~ 480 mm

---

Height	: 300 mm
Depth	: -
Weight	: 4.5 kg
Inputs	: 1 x high-strength cable gland (PG11)
Outputs	: -
Replacement voice coil	: -
Other features	: EN 54
Accessories	: supplied with safety rope for suspended installation
Packing dimensions (W x H x L)	: 0.57 x 0.36 x 0.57 m
Gross weight	: 7.66 kg
Net weight	: 5 kg