

STA-500 - Amplifier



Stereo PA-forstærker, 400 W, til generel anvendelse.

- Ventilatorcooling
- 2 x volumenkontrol
- Ground lift
- Højttalerforsinkelse
- Beskyttelseskredsløb med LED-indikator for beskyttelse mod kortslutning, overophedning og overspænding ved udgange
- Hver kanal har 1 LED-indikator for overbelastning (clip)

Technical data:

Peak output power	: 600 W
Power rating	: 400 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 200 W
Power rating at 8 Ohm	: 2 x 125 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1.3 V/55 kOhm
Attenuation factor	:
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: no
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: 64 dB
Crosstalk attenuation	: ? 55 dB
THD	: < 0.05%
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 730 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 95 mm

Depth	: 300 mm
Rack units, RU	: 2
Weight	: 6.6 kg
Connections	: 1 x 6.3 mm jack L/R 1 x RCA L/R 2 x SPEAKER 1 x 6.3 mm jack L/R 2 x pair of screw terminals

Packing dimensions (W x H x L)	: 0.37 x 0.14 x 0.51 m
Gross weight	: 7.45 kg
Net weight	: 6.64 kg