

STA-200D - Amplifier



Stereo class D PA-forstærker, 250 W,

- 5 justerbare line-indgange
- Lydløs i brug: blæserfrit kølesystem
- Med ringkernetransformer som giver høj effektreserve
- Forstærker med høj effekt
- 3,5 mm stereoindgang med justerbar følsomhed på frontpanel
- 4 RCA indgange
- 2 højttalerudgange
- 4 klemterminaler til højttalere
- 2 x volumenkontrol
- Beskyttet mod kortslutning, overspænding og overophedning
- LED-indikator for strøm, overbelastning (clip), beskyttelse og overophedning
- Ekstra slank og robust design, 1 U

Technical data:

Fanless	: 1
Peak output power	: 300 W
Power rating	: 250 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 125 W
Power rating at 8 Ohm	: 2 x 75 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1 \hat{A} V/23 \hat{A} kOhm (RCA), 90 mV-1 V (jack)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 100 dB(A)
Crosstalk attenuation	: ? 56 dB
THD	: < 0.05%
Phantom power	: -
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 350 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C

Width

: 483 mm





Height	: 44 mm
Depth	: 268 mm
Rack units, RU	: 1
Weight	: 5 kg
Connections	: 1 x 3.5 mm stereo jack 4 x RCA L/R 1 x SPEAKER L/R 1 x spring-load. speaker term. L/R
Packing dimensions (W x H x L)	: 0.34 x 0.1 x 0.46 m
Gross weight	: 5.9 kg
Net weight	: 5.15 kg