

CC-143 - Compact Connecting Terminal



Connecting terminal from WAGO

- 3-conductor terminal with operating levers
- Individually combinable wires and cross sections from 0.14 to 4 mm²
- Power rating: 450 V/32 A
- Continuous operating temperature: up to 85 °C
- Correct position of the conductor and stripping length can be visually checked due to transparent housing
- Two test slots for any standard test prod
- Of very compact size, thus, ideally suited for the application in confined spaces

Technical data:

Description	: connecting terminal
Type	: WAGO
Quantity	: 1
Features	: operating levers
Colour/colour coding	: transparent
Power rating	: 450 V/32 A
Insulating resistance	: -
Dielectric strength	: 4 kV
Certification	: UL, ABS, LR
Pole number	: 3
Cable inlet	: AWG 24-12
Suitable cable cross section	: flexible conductors: 0.14-4 mm ² rigid conductors: up to 0.2-4 mm ²
Connection	: 3-conductor terminal with operating levers
Strain relief	: -
Cable bending protection	: -
Stereo	: -
Mono	: -
Switches	: -
Material	: -
Central fixing	: -
Contact type	: -
No. of contacts	: -
Contact width	: -
Contact distance	: -
Admiss. ambient temp.	: 85 °C
Dimensions	: 18.7 x 8.3 x 18.6 mm
Diameter	: -
Length	: -
Weight	: 2.5 g
Other features	: -