

WALL-05SET/WS - Active Cabinets



Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

Technical data:

active	: 1
Master/slave	: 1
Active/passive	: active/passive
Transmission technology	: cable
Total output power	: 2 x 50 W
Power rating (RMS)	: 2 x 30 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 80-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 500 mV/20 kOhm (unbal.) 660 mV/40 kOhm (bal.)
System	: 2-way
Full range speaker	: -
Bass speaker	: 13 cm (5") bass speaker
Midrange speaker	: -
Tweeter	: dome tweeter
Number of speakers	: 2
Speaker size	: 13 cm (5")
SPL	: 89 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/100 VA
Dimensions	: 163 x 252 x 203 mm (with bracket)
Width	: 163 mm



Height	: 252 mm
Depth	: 203 mm
Weight	: 5.5Â kg (pair)
Inputs	: 1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spring-load. speaker term. (passive speaker system) spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: pair
Accessories	: -
Packing dimensions (W x H x L)	: 0.2 x 0.28 x 0.425 m
Gross weight	: 6.9 kg
Net weight	: 5.63 kg