

HSE-72 - Headworn Microphone



Elektret headsetmikrofon

- Kondensatorkapsel
- Cardioid karakteristik
- 3-polet mini XLR hunstik
- Svanehalsmikrofonarm
- Kompatibel med lommeseendere TXS-...HSE med 3-polet mini XLR stik
- Ekstern strømforsyning, fx via phantom strømforsyningsadapter EMA-1 eller EMA-300P
- Vindhætte

Technical data:

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 50-16,000 Hz
Nominal impedance	: 2 kOhm
Sensitivity	: 5.6 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 28 g
Cable	: -
Connection	: 3-pole mini XLR
Packing dimensions (W x H x L)	: 0.065 x 0.16 x 0.155 m
Gross weight	: 0.107 kg
Net weight	: 0.03 kg