

WAVE-10A - Active PA Speaker



Pure Entertainment!

The PA speaker systems of the WAVE series impress with a great sound and an attractive price. They are suitable for smaller to medium-sized function rooms and are the perfect starting equipment for entry-level DJs. The plastic cabinets of contemporary design are also lightweight and easy to use. Thus, they are ideally suited for mobile applications.

Active full range speaker system, 300 W

- Compact 10/2 full range bass-reflex system with plastic cabinet
- 25 cm (10") bass speaker and 25 mm (1") horn tweeter
- Integrated MP3 player with USB/SD slot
- Bluetooth receiver
- Infrared remote control
- Balanced mic input via XLR jack or 6.3 mm jack
- Line input via RCA jack or XLR jack
- 2-way tone control for treble and bass
- Mix out via XLR or 6.3 mm jack
- M8 threaded inserts for mounting support
- Stand sleeve

Technical data:

| | |
|--------------------------------|---|
| Low-impedance | : 1 |
| Active/passive | : active |
| Transmission technology | : wireless/cable |
| Total output power | : 300 W |
| Power rating (RMS) | : 150 W |
| Total power rating | : - |
| Power rating (RMS) | : - |
| Impedance | : - |
| Frequency range | : 60-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : 250 mV/7 kOhm (line, XLR, bal.), 150 mV/16 kOhm (line, RCA), 9.5 mV/0.8 kOhm (mic, XLR, bal.), 9.5 mV/0.8 kOhm (mic, 6.3 mm jack) |
| System | : 10/2 full range bass-reflex |
| Full range speaker | : - |
| Bass speaker | : 25 cm (10") bass speaker |
| Midrange speaker | : - |
| Tweeter | : 25 mm (1") horn tweeter |
| Number of speakers | : 2 |
| Speaker size | : 25 cm (10") |
| SPL | : 95 dB/W/m |
| Max. rated SPL | : 119 dB |
| Radiation angle/beam angle | : H: 90°/V: 60° |
| Radiation angle, horizontal | : 90° |
| Radiation angle, vertical | : 60° |
| Features | : - |
| Housing material | : plastic |
| Colour | : black |
| Mounting device | : M8 threaded inserts, stand sleeve |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/270 VA |
| Dimensions | : 300 x 510 x 250Å mm |
| Width | : 300 mm |
| Height | : 510 mm |

| | |
|--------------------------------|--|
| Depth | : 250 mm |
| Weight | : 9.4 kg |
| Inputs | : XLR or RCA L/R (line) XLR or 6.3 mm jack (mic) |
| Outputs | : XLR, bal. (parallel line out) |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.35 x 0.56 x 0.315 m |
| Gross weight | : 10.27 kg |
| Net weight | : 9.38 kg |