

PAM-10 - Amplifier



PA amplifier,
with zone paging microphone.

- Integrated amplifier 10 W
- Talk button and volume control, speaker connection 4-16 Ohm
- Power supply: \approx 230 V/50 Hz/12 VA
- Dimensions: 167 x 65 x 130 mm
- Mains operation

Technical data:

| | |
|---|----------------|
| Low-impedance | : 1 |
| Peak output power | : - |
| Power rating | : 10 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : 4-16 Ohm |
| Channels | : 1 |
| Zones | : - |
| Inputs | : - |
| Attenuation factor | : - |
| Frequency range | : 80-12,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : - |
| Crosstalk attenuation | : - |
| THD | : - |
| Phantom power | : - |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 12 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 167 mm |

| | |
|--------------------------------|--|
| Height | : 65 mm |
| Depth | : 130 mm |
| Rack units, RU | : - |
| Weight | : 1.14 kg |
| Connections | : electret gooseneck microphone, omnidirectional polar pattern speaker terminals |
| Packing dimensions (W x H x L) | : 0.145 x 0.2 x 0.175 m |
| Gross weight | : 1.35 kg |
| Net weight | : 1.14 kg |