

DRM-884RC - Paging Microphone



PA zone paging microphone,
for audio matrix router DRM-884.

- LCD for selected zones (1-32), volume and ID number
- LED indication for signal status
- Volume control (assignable for each zone)
- Zone selector control
- Momentary push-to-talk button
- Plug-in electret gooseneck microphone (NEUTRIK 3-pole XLR jack)
- USB port for loading sound files containing chimes
- Power supply via audio matrix router DRM-884
- Connection to DRM-884 via RJ45 jack and Cat. 5e network cable (supplied w/o cable), cable length up to 100 m

Technical data:

Description	: PA zone paging microphone
Version	: -
Transmission method	: cable
Polar pattern	: -
System	: -
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: -
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: 310 mm
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 176 x 70 x 162 mm
Weight	: 811 g
Cable	: -
Connection	: RJ45, micro USB
Packing dimensions (W x H x L)	: 0.255 x 0.105 x 0.395 m
Gross weight	: 1.197 kg
Net weight	: 0.811 kg