

PA-M4RC - PA Desk Microphone



PA zone paging microphone,
for PA matrix mixing amplifier PA-M224 or PA-M412.

- 4 zone selector switch
- ALL-CALL button
- Plug-in electret gooseneck microphone (3-pole XLR jack)
- Phantom power for gooseneck microphone
- LED indication for signal status
- Power supply via PA-M224 or PA-M412
- Connection to PA-M224 or PA-M412 via RJ45 jack and Cat. 5e network cable (copper, supplied w/o cable), cable length up to 200 m

Technical data:

Description	: PA zone paging microphone
Version	: -
Transmission method	: cable
Polar pattern	: -
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: via PA-M224, PA-M412
Operating time	: -
Audio frequency range	: 45-15,000 Hz
Nominal impedance	: -
Sensitivity	: 1 mV/Pa
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: 420 mm
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 140 x 65 x 205 mm
Weight	: 860 g
Cable	: -
Connection	: RJ45
Packing dimensions (W x H x L)	: 0.1 x 0.21 x 0.35 m
Gross weight	: 1.09 kg
Net weight	: 0.86 kg