

ETS-630DT - Dante PA Speaker Column



Active PA column speaker,
with integrated Dante(r) module.

- 30 W class D amplifier
- 6 x 7.6 cm (3") full range speaker
- Decoding: 16/24/32 bits
- Sampling rates: 44.1/48/88.2/96 kHz
- PoE (Power over Ethernet)
- 2 x M12 threaded bushing
- Metal cabinet with white metal front grille
- Supplied with mounting bracket

System requirements Dante(r): Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante(r) as well as the Dante(r) software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Technical data:

active	: 1
Dante ^(r)	: 1
Active/passive	: active
Transmission technology	: Dante ^(r)
Total output power	: -
Power rating (RMS)	: 30 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 120-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: Dante ^(r)
System	: full range
Full range speaker	: 6 x 7.6 cm
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 6
Speaker size	: 7.6 cm (3")
SPL	: 95 dB/W/m
Max. rated SPL	: 110 dB
Radiation angle/beam angle	: H: 120°/V: 40°
Radiation angle, horizontal	: 120°
Radiation angle, vertical	: 40°
Features	: -
Housing material	: metal
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: PoE
Dimensions	: 95 x 610 x 120 mm
Width	: 95 mm

Height	: 610 mm
Depth	: 120 mm
Weight	: 5.57 kg
Inputs	: RJ45
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.18 x 0.205 x 0.72 m
Gross weight	: 6.32 kg
Net weight	: 5.57 kg
Audio Codecs	: -
PoE	: -
LAN	: -
Software, app	: -
Sampling rates	: 44.1/48/88.2/96 kHz
Resolution	: 16/24/32 bits