

PA-924S - PA Amplifier



Mono PA power amplifier

- 1 x 240 W
- Temperature-controlled fan, continuously adjustable
- Protected against overheating, overload and short circuit
- LED indication for clip, protect, overtemperature, output level and 100 V/70 V
- Feed-through output (link)
- Speaker outputs via screw terminal contacts

Technical data:

| | |
|------------------------------------------|-----------------------------|
| 100 V | : 1 |
| Peak output power | : - |
| Power rating | : 240 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : 1 x 240 W |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : 70 V/20 Ohm, 100 V/40 Ohm |
| Channels | : 1 |
| Zones | : - |
| Inputs | : 650 mV/10 kOhm, balanced |
| Attenuation factor | : - |
| Frequency range | : 80-16,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 98 dB(A) |
| Crosstalk attenuation | : - |
| THD | : < 1% |
| Phantom power | : - |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 495 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 483 mm |



| | |
|--------------------------------|---------------------------------------------------------------------------------|
| Height | : 44 mm |
| Depth | : 255 mm |
| Rack units, RU | : 1 |
| Weight | : 3.8 kg |
| Connections | : 1 x combo 6.3 mm/XLR (input), 1 x XLR (link), screw contacts (speakers) |
| Packing dimensions (W x H x L) | : 0.36 x 0.14 x 0.54 m |
| Gross weight | : 4.93 kg |
| Net weight | : 3.99 kg |