

## PA-6000RC - PA Desk Microphone



PA zone paging desktop microphone,  
for connection to PA-6240, PA-6480 and PA-6600.

- Push-buttons for selecting speaker zones 1-6 and ALL-CALL function
- Start/pause function for 6 selectable announcements which are stored in the digital module PA-1120DMT
- Autom. chime via microphone announcement button
- Adjustable line input (RCA L/R) for connection of a signal source, e.g. CD player or tape deck
- LED indication for transmission mode
- Power supply via PA-6240, PA-6480, PA-6600
- RJ45 jack for connection to additional PA-6000RC microphones with slave/priority switch
- Supplied with connection module for PA-6240, PA-6480 and PA-6600

## Technical data:

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Description                    | : PA desktop microphone                 |
| Version                        | : -                                     |
| Transmission method            | : cable                                 |
| Polar pattern                  | : -                                     |
| System                         | : -                                     |
| Carrier frequency range        | : -                                     |
| Transmitting power             | : -                                     |
| Power supply                   | : via PA-1120, PA-1240                  |
| Operating time                 | : -                                     |
| Audio frequency range          | : -                                     |
| Nominal impedance              | : -                                     |
| Sensitivity                    | : -                                     |
| S/N ratio                      | : -                                     |
| Max. sound pressure            | : -                                     |
| Power supply                   | : -                                     |
| Gooseneck length               | : -                                     |
| Housing material               | : -                                     |
| Admiss. ambient temp.          | : 0-40 °C                               |
| Dimensions                     | : -                                     |
| Weight                         | : 1.45 kg                               |
| Cable                          | : -                                     |
| Connection                     | : RJ45 (master/slave) RCA L/R (line in) |
| Packing dimensions (W x H x L) | : 0.235 x 0.195 x 0.38 m                |
| Gross weight                   | : 1.757 kg                              |
| Net weight                     | : 1.451 kg                              |