

## EDL-530EN/WS - PA Loudspeaker



High-quality PA pendant speaker,  
with EN 54-24 certification.

- 100 V transmission technology or 8 Ohm operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

## Technical data:

100 V	: 1
Low-impedance	: 1
EN 54 certification	: 1
Active/passive	: passive
Transmission technology	: 100 V or low-impedance
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 30/15/7.5/3.8 W
Impedance	: 8 Ohm
Frequency range	: 65-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way coaxial
Full range speaker	: -
Bass speaker	: 13.33 cm (5.25")
Midrange speaker	: -
Tweeter	: 25 mm (1")
Number of speakers	: 2
Speaker size	: 13.33 cm (5.25")
SPL	: 90 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: eyelet bolt and 5 m safety rope with snap hook
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: Å~ 195 mm x 250 mm

Width	: ~ 195 mm
Height	: 250 mm
Depth	: -
Weight	: 2.26 kg
Inputs	: plug-in screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.22 x 0.3 x 0.22 m
Gross weight	: 2.66 kg
Net weight	: 2.26 kg