


SPE-140/WS - Loudspeaker



Indbygningshøjttaler, 10 W

- Dual membran for full range lyd gengivelse
- Slankt design
- Fast metal frontgitter
- Velegnet til indendørs annonceringer og baggrundsmusik

Technical data:

Impedance (Z)	: 4 Ohm
Transmission technology	: -
Frequency range	: 120-12,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 10 W
Peak music power output (MAX)	: 20 W
SPL	: 87 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: ~ 110 mm
Mounting depth	: 30 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: ~ 140 mm \times 40 mm
Outside diameter	: ~ 140 mm

Width	: Å~ 140 mm
Height	: -
Depth	: 40 mm
Colour	: white
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 311 g
Packing unit	: 1
Type of speaker	: 130
Packing dimensions (W x H x L)	: 0.145 x 0.045 x 0.145 m
Gross weight	: 0.344 kg
Net weight	: 0.311 kg
Low-impedance	: 1