


EDL-206 - PA Loudspeaker



Vejrbestandige indbygningshøjttalere

- 100 V line-teknologi
- Full range højttaler med dual membran, perfekte lydegenskaber
- Stænkæt, udført i et stykke hvidt plastik, polypropylenmembran i høj kvalitet med gummikant
- Til inden- og udendørs anvendelse
- Monteringsskruer i rustfrit stål medfølger

Technical data:

| | |
|---|---------------------------------|
| Impedance (Z) | : - |
| Transmission technology | : 100 V |
| Frequency range | : 85-18,000 Hz |
| Resonant frequency (fs) | : - |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : - |
| Power rating (RMS) | : 20/15/10/5/2.5 W |
| Peak music power output (MAX) | : - |
| SPL | : 90 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : - |
| Moving mass (Mms) | : - |
| Mech. Q factor (Qms) | : - |
| Electr. Q factor (Qes) | : - |
| Total Q factor (Qts) | : - |
| Equivalent volume (Vas) | : - |
| DC resistance (Re) | : - |
| Force factor (BxL) | : - |
| Voice coil induct. (Le) | : - |
| Voice coil diameter | : - |
| Voice coil former | : - |
| Linear excursion (X _{MAX}) | : - |
| Eff. cone area (Sd) | : - |
| Magnet weight | : - |
| Magnet diameter | : - |
| Mounting cutout | : \varnothing 132 mm |
| Mounting depth | : 110 mm |
| Mounting hole diameter | : - |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : \varnothing 180 mm x 130 mm |
| Outside diameter | : \varnothing 180 mm |

| | |
|--------------------------------|--------------------------|
| Width | : Å~ 180 mm |
| Height | : - |
| Depth | : 130 mm |
| Colour | : white |
| Protective class | : IP44 |
| Admiss. ambient temp. | : -30 °C to +40 °C |
| Weight | : 900 g |
| Packing unit | : 1 |
| Type of speaker | : 180 |
| Packing dimensions (W x H x L) | : 0.19 x 0.155 x 0.185 m |
| Gross weight | : 1.048 kg |
| Net weight | : 0.9 kg |
| weatherproof | : 1 |
| 100 V | : 1 |