

## PA-900 - PA Amplifier



### PA-mixerforstærker

- 1 x 120 W
- Lydløs i brug: blæserfrit kølesystem
- 4 balancerede mic/line-indgange
- Mic 1 med prioritet og automatisk talkover
- Mulighed for tilslutning af ekstra bordmikrofon via skrueterminal
- 1 aux indgang
- Højttalerudgange via skrueterminaler
- Line-udgang
- Mulighed for tilslutning af f.eks. effektenheder, equalizers, feedback controllers
- Volumenkontrol på ind- og udgange
- 2-vejs tonekontrol for udgangen
- 20 V phantom strømforsyning for hver mikrofonindgang
- Tilsluttes stikkontakt eller benytter 24 V nødstrømforsyning
- Aftagelige monteringsbeslag

## Technical data:

100 V	: 1
Low-impedance	: 1
Fanless	: 1
Peak output power	: 160 W
Power rating	: 120 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 120 W
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: 120 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: 4 Ohm
Channels	: 5
Zones	: -
Inputs	: 3 mV (mic), 200 mV (line), 140 mV (aux)
Attenuation factor	: -
Frequency range	: 50-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: $\pm 10\text{ dB}/100\text{ Hz}$
Equalizer midrange	: -
Equalizer treble	: $\pm 10\text{ dB}/10\text{ kHz}$
S/N ratio	: ? 80 dB
Crosstalk attenuation	: -
THD	: < 0.5%
Phantom power	: 20 V
Mains voltage	: $\sim 230\text{ V}$
Mains frequency	: 50 Hz
Power consumption, operation	: 300 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V

Power supply (possible  
alternative)

: DC 9 A





Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 88 mm
Depth	: 275 mm
Rack units, RU	: 2
Weight	: 9.9 kg
Connections	: 4 x XLR (mic/line), 1 x RCA L/R (aux), screw contacts (speakers)
Packing dimensions (W x H x L)	: 0.36 x 0.155 x 0.5 m
Gross weight	: 11.84 kg
Net weight	: 10.13 kg