

TXS-606HSE/2 - Microphone Transmitter



Multifrequency pocket transmitter,
with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Suitable for combination with headband/earband microphones and tie clip microphones with 3-pole mini XLR connector
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Technical data:

Multifrequency	: 1
General information	:
Description	: pocket transmitter
Carrier frequency range	: 672.000-691.975 MHz
Audio frequency range	: 30-18,000 Hz
Channels	: 1
THD	: -
Dynamic range	: -
Latency	:
RF S/N ratio	: -
Operating time	: ? 8 h
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	:
Transmitting power	: 10 mW
Operating range	: -
Power supply transmitter	: 2 x 1.5 V batt. AA size
Width transmitter	: 61 mm
Height transmitter	: 106 mm
Depth transmitter	: 27 mm
Weight transmitter	: 80 g
Connections transmitter	: 1 x 3-pole mini XLR
Specifications receiver	: -
Audio signal receiver	: -
Power supply receiver	: -
Width receiver	: -
Height receiver	: -
Depth receiver	: -
Weight receiver	: -
Connections receiver	: -