

## TXA-802PS - Charger



PWM quick-charge station,  
for simultaneously charging the rechargeable batteries (NC, NiMH) of one multifrequency pocket transmitter TXA-800HSE or the receiver TXA-800R and one hand-held microphone with multifrequency transmitter TXA-800HT.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 4-5 hours, e.g. for 1,600 mAh rech. batteries
- Each slot with LED for indicating battery charging status
- Supplied with plug-in PSU

## Technical data:

|                             |                            |
|-----------------------------|----------------------------|
| Category                    | : PWM quick-charge station |
| Input voltage               | : via suppl. power supply  |
| Output voltage              | : -                        |
| Output current              | : 380-460 mA               |
| Charging time               | : 4-5 h                    |
| Trickle charge              | : -                        |
| Polarity selection          | : -                        |
| Switchable output voltage   | : -                        |
| Reactivation                | : -                        |
| Connections                 | : -                        |
| Cable length                | : -                        |
| Short-circuit protection    | : -                        |
| Overload protection         | : -                        |
| Overheat protection         | : -                        |
| Reverse polarity protection | : -                        |
| Detection of faulty battery | : -                        |
| Protective class            | : -                        |
| Admiss. ambient temp.       | : 0-40 °C                  |
| Dimensions                  | : 84 x 90 x 106 mm         |
| Weight                      | : 200 g                    |
| Position                    | : -                        |
| Other features              | : -                        |