

AKB-160 - Amplifier Module

100V



Forstærkermodul, med 100 V output.

- 1 x 40 W
- Lydløs i brug: blæserfrit kølesystem
- Balanceret (XLR) og ubalanceret line-indgang (RCA)
- Højttalerudgang via klemterminaler
- Volumenkontrol
- Metalkabinet med monteringsbeslag

Technical data:

| | |
|--|--|
| 100 V | : 1 |
| Fanless | : 1 |
| Peak output power | : 60 W |
| Power rating | : 40 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : 40 W |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : - |
| Channels | : 1 |
| Zones | : - |
| Inputs | : 390 mV/26 kOhm, bal.420Â mV/11Â kOhm, unbal. |
| Attenuation factor | : - |
| Frequency range | : 17-20,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 80 dB |
| Crosstalk attenuation | : - |
| THD | : < 1% |
| Phantom power | : - |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 75 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |

Admiss. ambient temp.

: 0-40 °C





| | |
|--------------------------------|------------------------------------|
| Width | : 213 mm |
| Height | : 55 mm |
| Depth | : 238 mm |
| Rack units, RU | : - |
| Weight | : 3.2 kg |
| Connections | : 1 x XLR (line)1 x RCA L/R (line) |
| | |
| Packing dimensions (W x H x L) | : 0.29 x 0.11 x 0.305 m |
| Gross weight | : 3.6 kg |
| Net weight | : 3.23 kg |