

ECM-306BU/SW - Boundary Microphone



USB boundary microphone

- For operating directly at a PC or laptop
- No driver installation required, device will be identified automatically
- Integrated A/D converter: 48 kHz/16 bits
- Power LED
- Additional headphone connection: 3.5 mm jack
- 1.2 m connection cable with micro USB/USB Type-A plug
- Rear cutout for fixed installation (e.g. wall mounting)

Especially suitable for the use as a desktop microphone!

Technical data:

Description	: boundary microphone
Version	: USB
Transmission method	: cable
Polar pattern	: semi-cardioid
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 50-18,000 Hz
Nominal impedance	: -
Sensitivity	: 3.2 mV/Pa
S/N ratio	: 55 dB
Max. sound pressure	: 110 dB
Power supply	: DC 5 V via USB interface
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 90 x 25 x 90 mm
Weight	: 187 g
Cable	: 1.2 m
Connection	: micro USB/USB Type-A plug
Packing dimensions (W x H x L)	: 0.187 x 0.1455 x 0.057 m
Gross weight	: 0.38 kg
Net weight	: 0.225 kg
Audio Codecs	: -
PoE	: -
LAN	: -
Software, app	: -
Sampling rates	: 48 kHz
Resolution	: 16 Bit