


SA-200 - Amplifier



Universal stereoforstærker, 100 W

- Lydløs i brug: blæserfrit kølesystem
- Stereo line-indgang
- Højttalertilslutning via klemterminaler
- LED-indikator for overload (clip)
- Volumen
- 482 mm (19") rack installation, 1 U, monteringsbeslag medfølger

Technical data:

Fanless	: 1
Peak output power	: 2 x 100 W
Power rating	: 100 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 50 W
Power rating at 8 Ohm	: 2 x 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 420 mV/6 kOhm
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 83 dB
Crosstalk attenuation	: -
THD	: -
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 210 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 431 mm



Height	: 55 mm
Depth	: 255 mm
Rack units, RU	: 1
Weight	: 4.4 kg
Connections	: 1 x RCA L/R (line), 4 x spring-load. speaker term.(speakers)
Packing dimensions (W x H x L)	: 0.335 x 0.11 x 0.46 m
Gross weight	: 4.89 kg
Net weight	: 4.44 kg