


## SP-7W - Universal Loudspeaker



Universal speaker, 4 W, 8 Ohm

- Soft inverse suspension
- Slimline design

## Technical data:

Impedance (Z)	: 8 Ohm
Transmission technology	: -
Frequency range	: f3-10,000 Hz
Resonant frequency (fs)	: 160 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 4 W
Peak music power output (MAX)	: 7 W
SPL	: 86 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: 85 g
Magnet diameter	: Å~ 60 mm
Mounting cutout	: Å~ 95 mm
Mounting depth	: 38.5 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 102 x 102 x 40 mm
Outside diameter	: -

Width	: 102 mm
Height	: 102 mm
Depth	: 40 mm
Colour	: black
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.29 kg
Packing unit	: 1
Type of speaker	: 4"
Packing dimensions (W x H x L)	: 0.105 x 0.045 x 0.105 m
Gross weight	: 0.313 kg
Net weight	: 0.293 kg
Low-impedance	: 1