

KU-516 - Horn Driver



Weatherproof horn driver

- Diecast version, IP66
- Protected against powerful water jets
- 3.5 cm (1 1/4") mounting flange

Technical data:

| | |
|--------------------------------|---|
| Outdoors | : 1 |
| weatherproof | : 1 |
| Low-impedance | : 1 |
| Active/passive | : passive |
| Transmission technology | : - |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 75 W |
| Power rating (RMS) | : 50 W |
| Impedance | : 16 Ohm |
| Frequency range | : 160-6,500 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : - |
| SPL | : 113 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle/beam angle | : dep. on horn: SK-22, SK-159 |
| Radiation angle, horizontal | : dep. on horn |
| Radiation angle, vertical | : dep. on horn |
| Features | : - |
| Housing material | : diecast |
| Colour | : dark grey |
| Mounting device | : 3.5 mm mounting flange |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : $\sim 126\text{ mm} \times 100\text{ mm}$ |

| | |
|--------------------------------|-------------------------|
| Width | : Å~ 126 mm |
| Height | : - |
| Depth | : 100 mm |
| Weight | : 1.9 kg |
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : KU-516/VC |
| Other features | : weatherproof |
| Accessories | : |
| Packing dimensions (W x H x L) | : 0.14 x 0.115 x 0.14 m |
| Gross weight | : 2.25 kg |
| Net weight | : 1.95 kg |