

PA-1120DMT - Message/Timer Module



Digital message and timer insertion,
for PA mixing amplifiers with insertion compartment.

- Backlit DOT matrix display with 2 x 8 digits
- DCF77 synchronised clock (radio-controlled clock) for time-controlled announcements
- Internal memory for up to 26 audio files
- Audio files can be copied to the internal memory via integrated micro SD card reader
- 6 memory recall buttons, memory presets can also be accessed via floating contacts or via zone paging microphone PA-1120RC or PA-6000RC
- 3.5 mm connection on the front panel for picking up microphone signals or line signals
- Up to 20 daily events can be programmed

What is the maximum audio file size on a micro SD memory card(tm)

The maximum file size per memory location (M1 to M6) must not exceed 2176 kByte.

Technical data:

Description	: digital message and timer insertion
Nominal value	: -
Type	: -
Colour	: black
Material	: -
Suitable for	: PA mixing amplifiers with insertion compartment
Power supply	: DCÂ 15-17Â V/150Â mA
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 194 x 40 x 85 mm
Length	: -
Mounting dimensions	: -
Weight	: 270 g
Connections	: 3.5 mm jack
Other features	: integrated micro SD card reader
Packing unit	: 1
Packing dimensions (W x H x L)	: 0.175 x 0.06 x 0.225 m
Gross weight	: 0.524 kg
Net weight	: 0.431 kg