

TXA-820MT - Transmitter Module



Multifrequency transmitter module,
with UHF PLL technology.

For retrofitting amplifier systems of the TXA-820 series or for setting up wireless audio transmission paths.

- 16 selectable UHF frequencies (863-865 MHz)
- Volume control
- LCD for indicating selected channel/frequency
- LEDs for indicating carrier signal and audio signal

Licence-free in the EU.

Technical data:

Multifrequency	: 1
General information	:
Description	: multifrequency transmitter module
Carrier frequency range	: 863-865 MHz
Audio frequency range	: -
Channels	: 1
THD	: -
Dynamic range	: -
Latency	:
RF S/N ratio	: -
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	:
Transmitting power	: ≈ 10 mW
Operating range	: approx. 30 m
Power supply transmitter	: DC 12 V/120 mA
Width transmitter	: 88 mm
Height transmitter	: 37 mm
Depth transmitter	: 113 mm
Weight transmitter	: 80 g
Connections transmitter	: -
Specifications receiver	: -
Audio signal receiver	: -
Power supply receiver	: -
Width receiver	: -
Height receiver	: -
Depth receiver	: -
Weight receiver	: -
Connections receiver	: -