

ECM-300L - Electret Microphone



Elektret knaphulsmikrofon

- Ekstra kompakt udgave
- Phantom strømforsyning EMA-300P kan købes separat
- Med 6 m kabel og clip

Technical data:

| | |
|--------------------------------|----------------------------|
| Description | : lavalier microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : omnidir. |
| System | : electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 50-18,000 Hz |
| Nominal impedance | : 400 Ohm |
| Sensitivity | : 4 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 120 dB |
| Power supply | : via power supply adapter |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : Å~ 9 mm x 21 mm |
| Weight | : 4 g |
| Cable | : 6 m |
| Connection | : 3-pole mini XLR, unbal. |
| Packing dimensions (W x H x L) | : 0.11 x 0.06 x 0.24 m |
| Gross weight | : 0.28 kg |
| Net weight | : 0.078 kg |