


SA-230/SW - Amplifier



Universal stereo mixerforstærker, 50 W

SA-230/SW's overskuelige brugerflade gør det til en stor fornøjelse at lytte til - og især fremstille - musik. Tre stereo- og tre mikrofonindgange. Ved brug af særlige karaoke CD'er eller DVD'er er funktioner som "one-touch karaoke" eller "vocal partner" tilgængelige. Et justerbart digitalt ekko kan tilføjes som effekt til mikrofonindgangene. Forstærkerens blæserfri kølesystem sikrer, at den er lydløs i brug. De nyeste beskyttelseskredsløb beskytter mod overbelastning, overophedning og kortslutning.

- Lydløs i brug: blæserfrit kølesystem
- 3 stereo line-indgange
- 3 mikrofonindgange på frontpanel med gain kontrol
- Justerbart digitalt ekko til mikrofonindgange
- Karaoke funktion
- Vocal partner funktion
- LED-indikator for level kontrol og aktive line indgange
- Volumen-, bas-, diskant- og digitalt ekkokontrol
- Stereo optageudgang
- 482 mm (19") rack installation, 1 U, monteringsbeslag medfølger

Technical data:

| | |
|--|--|
| Fanless | : 1 |
| Peak output power | : 2 x 50 W |
| Power rating | : 50 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : 2 x 25 W |
| Power rating at 8 Ohm | : 2 x 20 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : - |
| Channels | : 2 |
| Zones | : - |
| Inputs | : 175 mV/8 kOhm (line) 2.5 mV/3.5 kOhm (mic) |
| Attenuation factor | : - |
| Frequency range | : 20-20,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : ± 10 dB |
| Equalizer midrange | : - |
| Equalizer treble | : ± 10 dB |
| S/N ratio | : 62 dB |
| Crosstalk attenuation | : - |
| THD | : - |
| Phantom power | : - |
| Mains voltage | : \approx 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 150 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |

Width

: 432 mm





| | |
|--------------------------------|--|
| Height | : 45 mm |
| Depth | : 275 mm |
| Rack units, RU | : 1 |
| Weight | : 3.8 kg |
| Connections | : 1 x RCA L/R (line), 1 x 6.3 mm jack (mic), 1 x RCA L/R (rec.), 4 x spring-load. speaker term. (speakers) |
| Packing dimensions (W x H x L) | : 0.27 x 0.055 x 0.43 m |
| Gross weight | : 4.42 kg |
| Net weight | : 3.86 kg |