

## MPX-44/SW - Stereo Mixer



**6-kanals DJ stereomixer**, med sort børstet aluminiumsfrontpanel.

- 6 indgange (4 stereoindgange, 2 mikrofonindgange)
- Stereoindgange, 2 x phono/line og 2 x line/line, med stereo LED level display
- Indgange med gain og 3-vejs equalizer, stereoindgange med cut funktion
- DJ mic med automatisk talkover, PAD og on-air taster
- Mic med PAD og on-air taster
- Taster lyser blå, når funktionen er aktiveret
- Justerbar, crossfader-styret hovedtelefonudgang med pre-fader listening (PFL) til stereoindgangene og mic
- Udskiftelig crossfader til crossfading mellem kanaler
- Særligt nemt glidende faders i høj kvalitet
- Master udgang med stereo LED level display
- Yderligere udgange: booth og zone
- Tilslutning for svanehalsslampe GNL-204 or GNL-205

## Technical data:

Input channels	: -
Number of mix/mono	: -
No. of stereo	: -
No. of channels	: 6
No. of inputs	: 12
Mic input	: 1.5 mV, 2 x 6.3 mm jack
Line input	: 150 mV, 5 x RCA L/R
CD input	: 150 mV, 1 x RCA L/R
Phono input	: 3 mV, 2 x RCA L/R
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 V/600 Ohm, 1 x 3-pole XLR, 1 x RCA L/R
Record output	: 0.5 V/600 Ohm, 1 x RCA L/R
Monitor output	: 1 V/600 Ohm (zone), 1 x RCA L/R
Booth output	: 1 V/600 Ohm, 1 x RCA L/R
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 8 Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: 12 V/0.75 W, 1 x BNC
WiFi	: -
USB	: -
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.1%
S/N ratio	: 61 dB, unweighted
Crosstalk	: -
Equalizer bass	: +12 dB, -12 dB/50 Hz (mic) +15 dB, -30 dB/50 Hz (channels 1-4)
Equalizer midrange	: +12 dB, -12 dB/1 kHz (mic) +15 dB, -30 dB/1 kHz (channels 1-4)
Equalizer treble	: +12 dB, -12 dB/10 kHz (mic) +15 dB, -30 dB/10 kHz (channels 1-4)
equalizer	: -

Talkover	: -16Â dB, automatic
Phantom power	: -
Crossfader	: yes
Media player	: -
Amplifier	: -
Power supply	: &acd;230Â V/50Â Hz/20Â VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 20 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 177 mm
Depth	: 105 mm
Rack units, RU	: 4
Weight	: 3.6 kg
Packing dimensions (W x H x L)	: 0.22 x 0.16 x 0.52 m
Gross weight	: 4.64 kg
Net weight	: 3.67 kg