

PA-1414MX - 10-Channel PA Pre-Amplifier



10-kanals PA-forforstærker

- 5 XLR indgange, mic/line
- 4 indgange, XLR mic/phono line
- 2 XLR master udgange
- 1 record udgang (master1, master2)
- Indgange med volumenkontrol og udgangsvælger (master1, master1+2, master2)
- Begge master udgange har 2-vejs tonekontrol
- Gongtaste med prioritet, mulighed for fjernbetjening, 2-toners eller 4-toners gong, sirene
- 1 push-to-talk tilslutning, RJ45, med prioritet (passer til PA-4000PTT)
- Low cut filter til hver mikrofonindgang
- Prioritet for kanaler 2-3
- Phantom strømforsyning til elektret mikrofoner kan tilsluttes XLR-indgangene
- Tilsluttes stikkontakt eller 24 V nødstrømforsyning

Technical data:

Peak output power	: -
Power rating	: -
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 10
Zones	: -
Inputs	: 2.5 mV, bal. (mic), 250 mV, bal. (line XLR), 250 mV, unbal. (line RCA)
Attenuation factor	:
Frequency range	: 20-20,000 Hz (-0.5 dB)
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10 dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/10 kHz
S/N ratio	: ? 60 dB (mic), ? 75 dB (line)
Crosstalk attenuation	: -
THD	: < 0.05%
Phantom power	: -
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 15 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 0.5 A

Admiss. ambient temp.

: 0-40 °C

Width

: 482 mm

Height

: 45 mm



MONACOR



Depth	: 240 mm
Rack units, RU	: 1
Weight	: 2.5 kg
Connections	: 9 x XLR (mic/line inputs), 4 x RCA L/R (line inputs), 1 x RJ45 (push-to-talk microphone), 2 x XLR (outputs), 1 x RCA L/R (record output)
Packing dimensions (W x H x L)	: 0.34 x 0.14 x 0.55 m
Gross weight	: 3.61 kg
Net weight	: 2.57 kg