

## PSUB-418AK - Active Subwoofer System



### PAK-400 serien

PAK-400 serien er velegnet til mange formål, udnytter moderne teknologi og en individuel lydindstilling, som opfylder flere forskellige behov. Forstærkersystemet er en kombination af class D til bassen og class A/B til hornet. Ved brug af presets er det nemt at finde den perfekte lyd og med high-pass filtret, som aktiveres ved 75 Hz, kan højttalerne nemt matches med subwooferen PSUB-418AK. **Aktiv PA-subwoofer, 1.000 W**

- Kompakt og let 46 cm (18") subwoofer med class D forstærker
- Kabinet af birkefiner med flange til montering på stativ, håndtag og hjul
- Basreflekssystem med lydtryk ved nominel effekt: 127 dB
- Justerbar delefrekvens: 60-150 Hz, gain, faseomskifter
- Balancerede indgange: kombineret XLR/6,3 mm og parallelle XLR udgange
- LED indikator for power, signal og peak/clip
- Flange til montering på stativ, håndtag, gummifødder
- Forsynet med hjul

### TASTENWELT 06/2015

"The PAK-400 series from IMG Stage Line features individual adjustment facilities using modern technology which makes it suitable for most versatile applications; definitely a concept that works: this series provides a perfect system for everyone, including keyboard entertainers, combinations of entertaining music and DJs."

## Technical data:

active	: 1
Active/passive	: active
Transmission technology	: cable
Total output power	: 1,000 W
Power rating (RMS)	: 600 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 35-150 Hz
THD	: -
S/N ratio	: -
Input signal	: 1.5 V/55 kOhm
System	: bass-reflex
Full range speaker	: -
Bass speaker	: 46 cm (18") bass speaker
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 46 cm (18")
SPL	: 97 dB/W/m
Max. rated SPL	: 127 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: birch plywood
Colour	: black
Mounting device	: stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230Â V/50Â Hz/840 VA
Dimensions	: 560 x 660 x 600 mm(w/o castors)
Width	: 560 mm
Height	: 660 mm

Depth	: 600 mm
Weight	: 38 kg
Inputs	: comb. XLR/6.3 mm input (L/R)
Outputs	: XLR: par. out (L/R)
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.68 x 0.74 x 0.83 m
Gross weight	: 44.4 kg
Net weight	: 38 kg