

## PAB-12WP/SW - PA Speaker Cabinet



**Vejrbestandig PA højttalere med IP-klassifikation.** Det rette valg, når der er brug for højttalere med høj lyd kvalitet og høj effekt, som kan tåle al slags vejr. Ideelle til permanent brug i det fri, fx i forlystelsesparker, i gågader, ved sportsarrangementer og andre steder, hvor det ikke er muligt at beskytte højttalerne mod vind og vejr. **Vejrbestandigt PA højttalersystem med høj effekt, 200 W, 8 Ohm**

- 2-vejs basreflekssystem i ABS-kabinet med høj ydeevne
- 30 cm (12") PA basenhed med imprægneret papirmembran
- 25 mm (1") horn
- Fremragende lydegenskaber
- Frontgitter med vandafvisende beklædning
- Speakon ind og parallel ud
- Metaldele af rustfrit stål
- 4 x M10 gevindindsats i top og bund til ophængning
- Flange til montering på stativ
- Testet og godkendt som boldskudssikre iht. DIN 18032, part 3

### Production Partner 04/2012

"With the PAB-12WP/SW, the product range of IMG Stage Line now includes a weatherproof (IP45) 12/2 speaker system. It is available at an attractive price yet has plenty to offer. The speaker system provides impressive test results and a great sound experience. Overall, the PAB-12WP/SW and the PAB-120WP/SW can definitely be recommended for purchase, especially if you need a solid 12/2 speaker system which is able to still operate effectively even under difficult boundary conditions." Test author Anselm Goertz

**tools4music 02/2012**

"[...] for users and service providers who are often working at outdoor events or have to attend permanent outdoor applications, the PAB-12WP/SW is definitely worth considering ... open-air event in the Rhineland area, Germany ... continuous rain, from light drizzle to downpour ... despite plenty of water, even from every angle, the PAB-12WP/SW provided a smooth performance throughout the 6-hour test. Soaking wet on the outside, bone-dry on the inside."

- + Pleasant sound - with impressive power reserves
- + Truly waterproof
- + Practice-orientated handling
- + Good workmanship

## Technical data:

Outdoors	: 1
weatherproof	: 1
Low-impedance	: 1
protected against ball rebound	: 1
Active/passive	: passive
Transmission technology	: -
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 400 W
Power rating (RMS)	: 200 W
Impedance	: 8 Ohm
Frequency range	: 42-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 30 cm (12") PA bass speaker
Midrange speaker	: -
Tweeter	: 25 mm (1") horn tweeter
Number of speakers	: 2
Speaker size	: 30 cm (12")
SPL	: 98 dB/W/m
Max. rated SPL	: 121 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS plastic
Colour	: black
Mounting device	: M10 threaded inserts, stand sleeve
Protected against ball rebound	: yes
Protection class	: IP45
Admiss. ambient temp.	: -10 °C to +40 °C
Power supply	: -

Dimensions	: 370 x 655 x 410 mm
Width	: 370 mm
Height	: 655 mm
Depth	: 410 mm
Weight	: 20.32 kg
Inputs	: 1 x SPEAKER
Outputs	: 1 x SPEAKER, par. out
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.47 x 0.73 x 0.43 m
Gross weight	: 25.36 kg
Net weight	: 20.32 kg