


MPT-142 - Piezo Tweeter



Piezo tweeter driver

- 3.5 cm (1 1/2") standard thread

Technical data:

Impedance (Z)	: ? 1,000 Ohm
Transmission technology	: -
Frequency range	: 1,800-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: -
Peak music power output (MAX)	: 115 W (8 Ohm system) 225 W (4 Ohm system)
SPL	: 92 dB/W/m
Max. rated SPL	: -
Max. voltage	: ~ 30 V
Radiation angle	: dep. on horn
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: not applicable
Mounting depth	: -
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: ~ 64 mm x 70 mm
Outside diameter	: -

Width	: 64 mm
Height	: -
Depth	: 70 mm
Colour	: black
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.057 kg
Packing unit	: 1
Type of speaker	: -
Packing dimensions (W x H x L)	: 0.08 x 0.08 x 0.07 m
Gross weight	: 0.06 kg
Net weight	: 0.057 kg
Low-impedance	: 1