AL-77HH/E2 - Wireless Microphone

Wireless microphone systems with push-on transmitter,
suitable for every dynamic microphone with XLR connection.

- 1 push-on transmitter, 1 receiver, 1 plug-in PSU, 1 connection cable with 6.3mm plug, 1 microphone holder
- True diversity system
- Volume and squelch controls
- LED indication for audio level and RF signal
- XLR output and 6.3mm jack output
- Supplied with dynamic microphone

Licence free in the EU.

Technical data:

Carrier frequency	: 863.625MHz
Transmitting power	: 5mW
RF S/N ratio	: 90dB
Audio range	: 50-15,000Hz, ±3dB
Dynamic range	: > 90dB
THD	: < 1%
Audio output	: 1V/5k Ohm (jack) 7/70mV/600 Ohm (XLR, bal.)
Operating range	: approx. 30m
Admiss. ambient temp.	: 0-50 °C
Power supply	
Transmitter	: 1.5V batt. AAA size (not supplied)
Receiver	: via suppl. PSU
Dimensions	
Transmitter	: Ø 54mm x 185mm (microphone) Ø 23mm x 90mm (push-on transmitter)
Receiver	: 220x45x135mm
Weight	
Transmitter	: 360g (microphone) 70g (push-on transmitter)
Receiver	: 345g
Connections	: 1 x 6.3mm jack, unbal. 1 x XLR, bal.