

MXR-6 - 6-Channel Audio Mixer



6-channel audio mixer,
with DSP effect unit, integrated MP3 player and Bluetooth receiver.

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 4 mono input channels with gain control, 2-way equalizer and pan pot
- 2 stereo input channels with 2-way equalizer and balance control
- MP3 player
- USB port
- Bluetooth receiver
- 16 adjustable delay effects
- Adjustable aux return input and FX send output
- +48 V phantom power, can be activated as required
- Adjustable headphone output
- Stereo LED level display
- Power is provided via USB or enclosed power supply

Technical data:

| | |
|--------------------|--|
| Bluetooth | : 1 |
| DSP | : 1 |
| Input channels | : 6 |
| Number of mix/mono | : 4 |
| No. of stereo | : 1 |
| No. of channels | : - |
| No. of inputs | : - |
| Mic input | : 2 mV, bal. 4 x XLR |
| Line input | : 100 mV (stereo), 2 x 6.3Â mm jack L/R 60 mV (mono), 2 x 6.3Â mm jack |
| CD input | : - |
| Phono input | : - |
| Tape (play) | : - |
| Aux input | : 400 mV, 1 x 6.3Â mm jack L/R |
| Insert input | : - |
| Effect return | : - |
| Master output | : 500 mV, 1 x 6.3Â mm jack L/R |
| Record output | : - |
| Monitor output | : - |
| Booth output | : - |
| Aux output | : - |
| Insert output | : - |
| Effect send | : 4.4 V, 1 x 6.3Â mm jack |
| Control room | : - |
| Tape (rec) | : - |
| Headphones | : 8 Ohm, 1 x 6.3Â mm jack |
| Gooseneck lamp | : - |
| WiFi | : - |
| USB | : yes |
| Bluetooth | : yes |
| Frequency range | : 20-20,000 Hz |
| THD | : < 0.03% |
| S/N ratio | : ? 83 dB(A) |
| Crosstalk | : - |
| Equalizer bass | : ±15 dB/80 Hz |
| Equalizer midrange | : - |

| | |
|--|-----------------------------|
| Equalizer treble | : ±15 dB/12 kHz |
| equalizer | : - |
| Talkover | : - |
| Phantom power | : +48 V |
| Crossfader | : - |
| Media player | : - |
| Amplifier | : - |
| Power supply | : USB or encl. power supply |
| Mains voltage | : - |
| Mains frequency | : - |
| Power consumption, operation | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 308 mm |
| Height | : 53 mm |
| Depth | : 205 mm |
| Rack units, RU | : - |
| Weight | : 1.9 kg |
| Packing dimensions (W x H x L) | : 0.33 x 0.24 x 0.08 m |
| Gross weight | : 2.1 kg |
| Net weight | : 1.93 kg |